



1.1

1.2

1.3

1.4

1		2		3							4									
l_1	d_1	l_2		d_3	d_4	h_1	h_2	h_3	h_4	Stroke										
120	M 10	M 12	20	25	32	40	50	63	80	16	32	29,5	2	41,5	2,5					
145	M 12	M 16	32	40	50	63	80	-	-	23	40	42	4	56	4					

Specification

- Handle
Zinc die casting
- Powder coated
Black, RAL 9005, textured finish ● **SW**
Silver, RAL 9006, textured finish ● **SR**
- Hub cover
Plastic
- Black for SW
- Light gray for SR
- Countersunk screw
Stainless steel
- Chemically blackened for SW
- Plain for SR
- **GN 126**
Threaded stud
Steel, blackened
- **GN 126.1**
Threaded stud
Stainless steel AISI 303
- *ISO Fundamental Tolerances* → Page 2151
- *Stainless Steel Characteristics* → Page 2166
- **RoHS**

On request

- With inch threads

Information

Flat adjustable tension levers GN 126 / GN 126.1 are characterized by their low height and the timelessly elegant design.

They are ideal whenever swiveling in a confined space is required or the lever is to be clamped in a particular position. The threaded insert / bored bushing is moveably attached to the handle with serrations.

Pulling the lever disengages the serrations, allowing it to be swiveled to the ideal clamping position. On “releasing” the handle, the serrations re-engage automatically.

see also...

- *Adjustable Hand Levers GN 300 (Threaded Stud Steel)* → Page 429
- *Adjustable Hand Levers GN 300.1 (Threaded Stud SST)* → Page 439
- *Adjustable Stainless Steel Hand Levers GN 300.5 (Matte Shot-Blasted)* → Page 441
- *Flat Adjustable Hand Levers GN 302* → Page 449
- *Flat Adjustable Tension Levers GN 125 (Threaded Stud Steel)* → Page 485
- *Flat Adjustable Stainless Steel Tension Levers GN 125.5* → Page 487

How to order (Threaded stud steel)

GN 126-145-M12-32-SW

1	l_1
2	d_1
3	l_2
4	Color

How to order (Threaded stud stainless steel)

GN 126.1-120-M10-40-SR

1	l_1
2	d_1
3	l_2
4	Color

2.1

2.2

2.3

2.4

