



3 Type

- C** angled lever with plain bore H7
- E** angled lever with threaded bore
- B*** straight lever with plain bore H7
- D*** straight lever with threaded bore

Steel												
d ₁	d ₂ Thread Type E / D	d ₃ H7 Bore Type C / B	d ₄	d ₅	h ₁	h ₂ ≈ Type C Type E	Type B Type D	l ₁ ≈ Type C Type E	Type B Type D	l ₂ ≈	t ₁ min.	t ₂ min.
22	M 10	B 10	8	20	37	67	40,5	89,5	96	85	15	19
25	M 12	B 12	10	25	42	76	47	100,5	107,5	95	18	21
28	M 12	B 12	12	30	47	87	53	114	122	108	18	23
32	M 16	B 16	12	32	52	98	59	133	142	126	23	28
36	M 16	B 16	14	35	58	108	64,5	146	156	138	24	28
40	M 20	B 20	16	40	64	120	72	162,5	174	154	27	30

Stainless Steel									
d ₁	d ₂ only type E	d ₄	d ₅	h ₁	h ₂ ≈	l ₁ ≈	l ₂ ≈	t ₁ min.	
22	M 8	8	20	37	67	89,5	85	18	
25	M 10	10	25	42	76	100,5	95	18	
28	M 12	12	30	47	87	114	108	20	
32	M 16	12	32	52	98	133	126	25	

* not available from stock, requires a minimum order quantity

Specification

- Steel —
- Stainless Steel **NI**
 - AISI 303
 - matte shot-blasted
- Ball knobs DIN 319
Plastic, Duroplast
black, shiny finish
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS

Information

Tension levers GN 212 are used as clamping element as well as operating levers.

see also...

- Adjustable tension levers GN 212.3 (Steel, blackened) → Page 346
- Adjustable Stainless Steel-Tension levers GN 212.5 → Page 348

How to order (Steel)	
1	d ₁
2	d ₃ (d ₂)
3	Type

GN 212-28-B12-C

How to order (Stainless Steel)	
1	d ₁
2	d ₂
3	Type
4	Material

GN 212-25-M10-E-NI