



1	2			3	4	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke	t min.
l <sub>1</sub>	d <sub>1</sub>			d <sub>3</sub>	d <sub>4</sub>					
30	M 3	-	-	10	13	26,5	4	31	3,5	7
30	M 4	M 5	M 6	10	13	26,5	4	31	3,5	8
45	M 4	M 5	M 6	10	13	26,5	4	35	3,5	8
63	M 6	M 8	-	13,5	17,5	32,5	6,5	45	4	11
78	M 8	M 10	-	16	21	37,5	8	55	4	14

**Specification**

**Handle**

Zinc die casting  
 Powder coated  
 Black, RAL 9005, textured finish ● SW

**Insert**

Stainless steel AISI 303

**Releasing button**

Plastic, Polyamide (PA)  
 • Black, RAL 9005 ● S  
 • Orange, RAL 2004 ● O  
 • Gray, RAL 7035 ● G

RoHS

**On request**

Handle in GN 300 colors

Adjustable hand levers GN 303.1 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be dis-engaged. The releasing button is a design element that offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

**GN 303** Adjustable hand levers (with push button, bushing Steel) QVX

**Technical Information**

Stainless Steel Characteristics QVX

How to order

1	l <sub>1</sub>
2	Connection thread d <sub>1</sub>
3	Color handle
4	Color releasing button

GN303.1-78-M10-SW-S

1.1  
1.2  
1.3  
1.4  
2.2  
2.3  
2.4

