



1

2

l_1	d_1 H7 Bore	d_2	b_1	b_2	h_1	h_2	$h_3 \approx$	l_2	t min.	\varnothing Handle
65	B 8	13	19	22	18	23	40	23	13	18
80	B 10	14	20	24	20	26	40	30	16	18
95	B 10	14	22	26	22	29	50	36	19	21
110	B 12	18	22	28	24	34	65	44	18	23
140	B 12	18	24	30	26	37	80	57	18	26

Specification

- Body
Plastic
Duroplast (Phenolic PF)
 - Reinforced
 - Temperature resistant up to 110 °C
 - Black, shiny finish
- Hub bushing
Steel, blackened
- Threaded bushing to accept the revolving handle
Brass
- Revolving handles GN 598
 - Plastic, Duroplast
 - Black, shiny finish
 - Spindle steel
 - Zinc plated, blue passivated
- ISO Fundamental Tolerances → Page 2151
- RoHS

Information

Cranked handles GN 510 allow fine adjustment.

These cranked handles are fitted to shaft with a cross pin. To simplify the installation there is a centred drilling on both sides.

see also...

- Control Handles GN 112.1 (Zinc Die Casting) → Page 298
- Tri-Ball Handles GN 10 (Steel, Zinc Plated) → Page 299

How to order

GN 510-80-B10

1 l_1 2 d_1