



ELESA Original design L.652

Length l	Nominal dimension	Actual dimension	1	2	d ₃	h ₁	h ₂	s Square	t min.
			d ₁ H9 Bore B	d ₂ Thread					
40	40	41	-	M 5	-	28	18,5	13	16
40	40	41	B 6	M 6	9	28	18,5	13	16
55	55	56,5	-	M 5	-	33	21,5	15	15
55	55	56,5	B 6	M 6	10	33	21,5	15	18
55	55	56,5	-	M 8	10	33	21,5	15	18
67	67	68,5	B 6	-	11	37	24,5	16,5	20
67	67	68,5	B 8	M 8	11	37	24,5	16,5	20
67	67	68,5	-	M 10	-	37	24,5	16,5	20
80	80	82	B 6	-	14	41,5	25	20	25
80	80	82	B 8	M 8	14	41,5	25	20	25
80	80	82	-	M 10	14	41,5	25	20	25
80	80	82	-	M 12	14	41,5	25	20	18
93	93	94	B 6	-	15	46	28,5	21	25
93	93	94	-	M 10	15	46	28,5	21	25
93	93	94	-	M 12	15	46	28,5	21	18

Specification

- Plastic
Technopolymer (Polyamide PA)
- glass fiber re-inforced
- temperature resistant up to 130 °C
- black, matte finish

• Bushing brass

• ISO-Fundamental tolerances → Page 1479

• Plastic characteristics → Page 1483

• RoHS

On request

- T-Handles in orange or red

Information

GN 563 T-Handles can be used on operating handles as well as on clamping fixtures. These handles lend themselves ideally for very high manual clamping forces.

see also...

- T-Handles GN 563.2 (Aluminum) → Page 66

How to order

GN 563-80-B8

1 Length l

2 d₁ (d₂)