



**2** Type  
**A** without spanner  
**B** with spanner

**1**

d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h	k <sub>1</sub>	k <sub>2</sub>	Length l	Nominal load (WLL)
M 6	13	23	28	20	37	7	37	9	0,1 t [1,0 kN]
M 8	16	25	30	25	46	9	47	12	0,3 t [3,0 kN]
M 10	16	25	30	25	46	9	47	15	0,4 t [4,0 kN]
M 12	20	30	34	30	55	10	56	18	0,75 t [7,5 kN]
M 16	23,5	36	40	35	64	13	65	24	1,5 t [15,0 kN]
M 20	29	41	50	40	75	16	76	30	2,3 t [23,0 kN]
M 24	35	51	60	49	90	19	92	36	3,2 t [32,0 kN]
M 30	44	66	75	60	113	24	114	45	4,5 t [45,0 kN]
M 36	53	75	90	72	135	29	135	54	7,0 t [70,0 kN]

**Specification**

- Ring  
 Steel, German Material No. 1.6541  
 - forged  
 - high-tensile tempered  
 100 % electro magnetic tensile tested to EN 1677  
 - plastic coated, pink
- Bolt  
 Steel  
 - Tensile strength class 10.9  
 - 100 % electro magnetic tensile tested
- *Strength values of screws* → Page 1481
- RoHS

**Information**

The lifting eye bolts GN 581 are mounted in rotating bearings, allowing the direction of the force action to be adjusted and preventing inadvertent loosening or overturning (as potentially possible in lifting eye bolts DIN 580).

Lifting eye bolts GN 581 offer a high load carrying capacity and they are tested to meet safety standards (safety factor 4).

The rated load carrying capacity listed in the above table is clearly marked on the ring. It applies to the most unfavourable load application of the load types listed opposite.

Lifting eye bolts GN 581 comply with Mechanical Engineering Directive 2006 / 42 / EG and are BG tested.

The integrated RFID transponder clearly marks and identifies the sling and lifting gear, e.g. during the prescribed regular inspection.

The hexagon socket bolt cannot be removed from the ring.

Type B is suitable for assembly without the need to use tools: inserting the spanner in the hexagon socket of the bolt allows the bolt to be turned in and out by hand.

see also...  
 Stainless Steel-Lifting eye bolts GN 581.5 → Page 1064

How to order	<b>1</b> d <sub>1</sub>
	<b>2</b> Type

**GN 581-M12-A**



Method of mounting										
Number	1	1	2	2	2	2	2	3 and 4	3 and 4	3 and 4
Angles of inclination	0°	90°	0°	90°	0 to 45°	45 to 60°	asymm.	0 to 45°	45 to 60°	asymm.
Factor	1	1	2	2	1,4	1	1	2,1	1,5	1
M 6	0,50	0,10 t	1,00	0,20 t	0,14	0,10 t	0,10 t	0,21 t	0,15 t	0,10 t
M 8	1,00 [0,14]	0,30 t	2,00 [0,28]	0,60 t	0,42 [0,10]	0,30 t	0,30 t	0,63 t	0,45 t	0,30 t
M 10	1,00 [0,23]	0,40 t	2,00 [0,46]	0,80 t	0,56 [0,17]	0,40 t	0,40 t	0,84 t	0,60 t	0,40 t
M 12	2,00 [0,34]	0,75 t	4,00 [0,68]	1,50 t	1,00 [0,24]	0,75 t	0,75 t	1,60 t	1,12 t	0,75 t
M 16	4,00 [0,70]	1,50 t	8,00 [1,40]	3,00 t	2,10 [0,50]	1,50 t	1,50 t	3,15 t	2,25 t	1,50 t
M 20	6,00 [1,20]	2,30 t	12,00 [2,40]	4,60 t	3,22 [0,86]	2,30 t	2,30 t	4,83 t	3,45 t	2,30 t
M 24	8,00 [1,80]	3,20 t	16,00 [3,60]	6,40 t	4,48 [1,29]	3,20 t	3,20 t	6,70 t	4,80 t	3,20 t
M 30	12,00 [3,20]	4,50 t	24,00 [6,40]	9,00 t	6,30 [2,30]	4,50 t	4,50 t	9,40 t	6,70 t	4,50 t
M 36	16,00 [4,60]	7,00 t	32,00 [9,20]	14,00 t	9,80 [3,30]	7,00 t	7,00 t	14,70 t	10,50 t	7,00 t

**Safety instructions**

The loads given in brackets refer to the load capacity of the corresponding lifting eye bolt DIN 580. If such a value is not indicated the use of the lifting eye bolts DIN 580 is not permitted!

The bolt-on surface for the lifting eye bolts GN 581 must be plane and at a right angle to the threaded borehole; the counter-sinking must be ≤ the nominal diameter of the thread.

Screwed in, the collar of the screw must make firm contact (do not use washers) and the eye bolt must rotate freely by 360°.

Before applying the load, turn the lifting eye bolt in the direction of the force. The lifting eye bolt is not suitable for frequent rotation cycles under load.

The specified load values apply for a minimum screw-in length of 1,5 × nominal thread diameter in steel with a minimum tensile strength of 37 kp/mm², at an ambient temperature of - 40° C to + 100° C. Load-bearing capacity under different conditions upon request.

Operating instructions with more details and specifications are included with every delivery (see also [www.ganter-griff.com](http://www.ganter-griff.com)).