



1

2

d_1	Length l	e	h_1	h_2	h_3	h_4	k_1	k_2	k_3	k_4	A/F	Tightening torque in Nm	Nominal load in t
M 8	13	30	84	76	31	45	8	45	29	44	27	10	0,30
M 10	17	34	86	78	31	47	8	45	29	44	30	10	0,45
M 12	21	42	117	107	49	58	10	55	35	65	36	10	0,60
M 16	25	48	127	114	46	68	13	64	38	65	41	30	1,30
M 20	33	62	150	137	54	83	13	61	35	77	55	70	2,00
M 24	40	81	191	173	66	107	18	76	40	94	70	150	3,50
M 30	50	99	243	221	90	131	22	94	50	126	85	225	5,00

Specification

- Chain ring
Steel, German Material No. 1.6540
 - High-tensile tempered
 - 100% electro magnetic tensile tested
 - Powder coated, pink
- Eye ring
Steel, German Material No. 1.6541
 - Forged, high-tensile tempered
 - 100% electro magnetic tensile tested
 - Powder coated, pink
- Bearing case
Steel 1.6541
 - Forged, high-tensile tempered
 - 100% electro magnetic tensile tested
 - Zinc plated, blue passivated
- Screw
Steel, property class 10.9
Finish: Delta Tone

• *Strength Values of Screws* → Page 2152

• RoHS

On request

- Other screw lengths

Information

Load rings GN 5860 rotate running in ball bearings. The freely rotating ring allows the bolts to hold loads in any tensile direction.

The rated load-bearing capacity is shown clearly on the swivel eye bolt. It is valid for the most unfavourable case in terms of the types of load listed opposite. Load rings GN 5860 comply with Mechanical Engineering Directive 2006 / 42 / EG and are BG tested.

The integrated RFID transponder clearly marks and identifies the sling and lifting gear, e.g. during the prescribed regular inspection.

see also...

- *Load Hooks GN 5862* → Page 1514
- *Shackles GN 584* → Page 1520
- *Shackles GN 585* → Page 1521

How to order

GN 5860-M12-21

1 d_1

2 Length l



Method of mounting										
Number	1	1	2	2	2	2	2	3 and 4	3 and 4	3 and 4
Angles of inclination	0°	90°	0°	90°	0 to 45°	45 to 60°	asymm.	0 to 45°	45 to 60°	asymm.
Factor	1	1	2	2	1,4	1	1	2,1	1,5	1
M 8	0,60 t	0,30 t	1,20 t	0,60 t	0,42 t	0,30 t	0,30 t	0,63 t	0,45 t	0,30 t
M 10	0,90 t	0,45 t	1,80 t	0,90 t	0,63 t	0,40 t	0,40 t	0,94 t	0,67 t	0,40 t
M 12	1,20 t	0,60 t	2,40 t	1,20 t	0,84 t	0,60 t	0,60 t	1,26 t	0,90 t	0,60 t
M 16	2,60 t	1,30 t	5,20 t	2,60 t	1,82 t	1,30 t	1,30 t	2,73 t	1,95 t	1,30 t
M 20	4,00 t	2,00 t	8,00 t	4,00 t	2,80 t	2,00 t	2,00 t	4,25 t	3,00 t	2,00 t
M 24	7,00 t	3,50 t	14,00 t	7,00 t	4,90 t	3,50 t	3,50 t	7,35 t	5,25 t	3,50 t
M 30	10,00 t	5,00 t	20,00 t	10,00 t	7,00 t	5,00 t	5,00 t	10,50 t	7,50 t	5,00 t

Safety instructions

The above load capacity table shows the maximum loads in metric tonnes as factor of the load ring type and at an operating temperature range of -40 °C to +100 °C, with a safety coefficient of 4 taken into account for all values.

The load ring GN 5860 may be used only if it is bolted with the minimum screw-in depth which depends on the material and if the bolt contact surface is plane and fixed at a right angle to the tap hole.

If permanently mounted in place, the swivel eye bolt must rotate freely by 360° and must not rest on edges or other fixture, e.g. crane hooks. The load rings are not suitable for permanent rotary movement under load exposure.

The operating instruction contains further guidelines and is included with every load ring (see also at www.ganternorm.com/en/service).

