



1

2

d ₁	Length l - Thread length b ₁				b ₂	d ₂
	l - b ₁	l - b ₁	l - b ₁	l - b ₁		
M 6	50 - 30	80 - 50	-	-	9	5,3
M 8	40 - 20	63 - 40	100 - 63	-	11	7,1
M 10	50 - 25	80 - 50	125 - 75	200 - 125	13	9
M 12	50 - 25	80 - 50	125 - 75	200 - 125	15	10,7
M 14	63 - 32	100 - 63	160 - 100	250 - 160	17	12,6
M 16	63 - 32	100 - 63	160 - 100	250 - 160	19	14,6
M 20	80 - 32	125 - 70	200 - 125	315 - 190	27	18,2
M 24	100 - 50	160 - 100	250 - 160	400 - 250	35	21,9

Specification

- Heat-treatable Steel
 - M 6 ... M12: Tensile strength class 10.9
 - M14 ... M24: Tensile strength class 8.8
 - blackened
- *Strength values of screws* → Page 1481
- RoHS

Information

Studs DIN 6379 are mainly used in DIN 508, DIN 6330 and washers DIN 6430 to form a complete clamp unit.

see also...

- *T-Nuts DIN 508* → Page 864

How to order

DIN 6379-M12-125

1 d₁

2 Length l