



3.1  
3.2  
3.3

<b>d<sub>1</sub></b>	<b>d<sub>2</sub> H10</b>		<b>b<sub>1</sub></b>	<b>b<sub>2</sub></b>	<b>d<sub>3</sub></b>	<b>s</b>	<b>x ≈</b> Max. protrusion of cap screw	Adjustable hand lever for d <sub>3</sub>
30	B 12	-	11	13	M 4	2,1	0,7	GN 311-30-M4-12-SW
32	B 14	-	11	13	M 4	2,1	0,7	GN 311-30-M4-12-SW
36	B 15	B 16	13	15	M 5	2,1	1,4	GN 311-30-M5-13-SW
42	B 18	B 20	15	18	M 5	3	0,6	GN 311-30-M5-15-SW
48	B 22	B 25	15	18	M 5	3	0	GN 311-45-M5-16-SW
55	B 28	B 30	15	18	M 6	3	0,5	GN 311-45-M6-18-SW
60	B 32	B 35	15	18	M 6	4	0,4	GN 311-45-M6-19-SW
65	B 40	-	15	18	M 6	4	0,5	GN 311-45-M6-20-SW

\* recommended diameter tolerance

**Specification**

- Stainless steel AISI 316LHC Sintered **NI**
- Damping washer Elastomer (PUR) - 70 Shore A - Temperature resistant up to 80 °C - Transparent
- Socket cap screw DIN 912 Stainless steel AISI 304
- *ISO Fundamental Tolerances* → Page 2151
- *Plastic Characteristics* → Page 2158
- *Stainless Steel Characteristics* → Page 2166
- RoHS

**Accessory**

- Adjustable Hand Levers GN 311 → Page 1159

**Information**

The affixed damping washer of the split shaft collars GN 7072.3 absorbs mild shocks and has a sound-damping effect when the shaft collars come into contact with other components.

They can be assembled safely and easily with a high clamping force by reducing the slot height, without damaging the surface of shafts and axles. As compared to semi-split shaft collars, split shaft collars can even be assembled radially.

The thread d<sub>3</sub> for sizes d<sub>1</sub> = 30 to 36 is designed as a through hole; for sizes d<sub>1</sub> = 42 and larger, it is designed as blind hole.

see also...

- *Semi-Split Shaft Collars GN 7062.3 (with Damping Washer)* → Page 1151
- *Split Shaft Collars GN 707.2* → Page 1154

3.4  
3.5  
3.6  
3.7  
3.8  
3.9

**How to order**

**GN 7072.3-42-B18-NI**

1	d <sub>1</sub>
2	d <sub>2</sub>
3	Material