



Inox
Stainless
Steel

2

d ₁	d ₂	d ₃	l ₁ ≈	l ₂	l ₃	l ₄ ≈	l ₅
16	M 5	16	58	15	5	52,5	9,5
18	M 5	16	72,5	15	5	67	9,5
22	M 6	20	80,5	19,5	6	74	10,5
24	M 6	20	95,5	19,5	6	89	10,5
25	M 6	20	105,5	19,5	6	98,5	10,5

Specification

- Handle
Plastic
Technopolymer (Polyamide PA)
- temperature resistant up to 90 °C
- black, matte
- revolving

- **GN 798.3**
Retractable mechanism
Steel
blackened

- **GN 798.5**
Retractable mechanism
Stainless Steel
- Axle parts AISI 303
- Flat base
Sintered Steel AISI 316 LHC

• Plastic characteristics → Page 1483

• Stainless Steel characteristics → Page 1489

• RoHS

1

KT

Information

Typical in design are the retractable handles GN 798.3 / GN 798.5 with their stepped shape consisting of two cylinders giving the operator a better grip, especially when pulling the handle out from its locked position before it can be folded back into the rest position.

Retractable handles GN 798.3 / GN 798.5 are suitable when the handle must be withdrawn during automatic operations.

How to order (Retractable mechanism steel)

1 2
GN 798.3-KT-22

1 Material

2 d₁

How to order (Retractable mechanism St. Steel)

1 2
GN 798.5-KT-25

1 Material

2 d₁