



ROSTFREI  
Inox  
Stainless  
Steel

d <sub>1</sub>	l <sub>1</sub>	d <sub>2</sub> -0,07	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	k <sub>1</sub>	k <sub>2</sub>	k <sub>3</sub>	l <sub>2</sub>	l <sub>3</sub>	Nominal load in kN *			
													F <sub>1</sub> ST	NI	F <sub>2</sub>	F <sub>3</sub>
M 8	12	6,62	21,5	87,5	36	25,7	27	9,5	49	30	17,8	8	2,1	2,1	0,9	0,8
M 10	14	8,35	21,5	87,5	36	25,7	27	9,5	49	30	20	10	3,9	3,9	1,5	1,5
M 12	17	10,07	21,5	87,5	36	25,7	27	9,5	49	30	24	12	6,2	6,2	2,5	2,3
M 16	17	13,8	21,5	87,5	36	25,7	27	9,5	49	30	24	12	8,4	8,4	4,5	4,2
M 20	22	17,25	30	114	52	36,5	32,6	15	56	36	30	17	16,6	10	7,7	5

\* Testing according to DIN EN 13155

**Specification**

**Pin**

- Steel **ST**
- Heat-treated, manganese phosphated
- Stainless steel AISI 630 **NI**
- Precipitation hardened

**Shackle**

- Steel at ST
- Heat-treated, manganese phosphated
- Stainless steel AISI 316Ti at NI

**Threaded segments**

- Stainless steel AISI 630
- Precipitation-hardened

**Push button**

- Aluminum, red anodized

**Spring**

- Stainless steel

RoHS

Threaded lifting pins GN 1133 are support elements designed for quick and easy use. Pressing the operation button unlocks the threaded segments, allowing the pin to be moved in or out of the mounting thread. This eliminates the time-consuming process of screwing in or out encountered with typical lifting gear, such as lifting eye bolts.

Assuming sufficient material strength, only true-to-gauge threaded holes are required to make use of the threaded lifting pins.

The shackle swivels 180°, with a safety bar protecting the button from unintentional operation.

For further application guidelines, see the operating instructions enclosed with every threaded lifting pin ([ganternorm.com/en/service](http://ganternorm.com/en/service)).

**Technical Information**

Stainless Steel Characteristics

Page

QVX

How to order

**GN 1133-M8-12-ST**

1	d <sub>1</sub>
2	l <sub>1</sub>
3	Material