



1	Type
DK	With triangular spindle
VK	With square spindle
SCH	With slot
SK	With wing knob
SCK	With wing knob, lockable (same lock)
SC	With key (same lock)

Latch arm distance A			d	
			Type DK / VK / SCH	Type SK / SCK / SC
7,5	13,5	19,5	20	22

Specification

- Lock housing
 - Zinc die casting
 - Housing collar chrome plated
 - Housing collar
 - Powder coated
 - Black, RAL 9005, textured finish
- Wing knob
 - Zinc die casting
 - Powder coated
 - Black, RAL 9005, textured finish
- Key
 - Nickel silver with plastic hand piece
- Other parts
 - Steel zinc plated, blue passivated
- Protection class IP65
- Type DK / VK / SCH / SK
- IP Protection Classes → Page 2153
- Stainless Steel Characteristics → Page 2166
- RoHS

Accessories

- Socket Keys 119.2 → Page 1266
- Protective Caps GN 120 → Page 1268

On request

- Lock with Different Combinations

Information

Latches GN 115.1 have smaller dimensions than standard latches GN 115, making them ideal for applications with limited space or requiring an unobtrusive appearance.

They lock by a turning operation limited to 90° which moves the latch arm in the locked position behind the door frame. The bevels of the latch arm ease the closing of the door.

Latch arms are available with different bend angles to cover a latch arm distance A of 7,5 / 13,5 and 19,5 mm.

The lockable latches (Types SCK and SC) are delivered with 2 keys. The key may be pulled off in both end positions. The lock is standard, so that every lock can be opened with the same key.

The latches GN 115.1 are supplied with loosely enclosed latch arm (except for type SC).

see also...

- List of Latch Types → Page 1196 ff.
- Latches GN 115.6 (Stainless Steel, Small Type) → Page 1212

How to order (Housing collar chrome plated)		1	Type
GN 115.1-SK-13,5		2	Latch arm distance A

How to order (Housing collar black)		1	Type
GN 115.1-SC-7,5-SW		2	Latch arm distance A
		3	Finish