



- 3 Type**
- A** Without scale
 - AS** With scale 0...50
60 graduations

1

2

d ₁	d ₂ H7 Bore with keyway			d ₃	d ₅	d ₆ P.C.D. Ø for fixing screws Page 353	l ₁	l ₂	l ₃ Bore length Page 353	w Stroke
44	K 10	K 12	-	33	23	33	37	6	31	4
52	K 12	K 14	K 16	42	31,5	41,8	37,5	6	31,5	4

Specification

4

- Stainless steel AISI 303 **NI**
- Type AS:
 - Scale engraved with laser precision, black
 - Reference line on location ring
- Keyway P9 DIN 6885
 - Page 1 for bore K 10 → Page 2078
 - Page 2 for bores > K 10 → Page 2079
- ISO Fundamental Tolerances → Page 2151
- Stainless Steel Characteristics → Page 2166
- RoHS

On request

- Special graduations see „How to Order Graduations“ → Page 326

Information

Indexing mechanisms GN 200 replace and simplify complicated indexing and safety mechanisms.

Besides the standard scale (Type AS) the control knob version may be supplied with any scale.

Regarding design, numbering run, numbering position and numbering sequence of the scale please see the layout for scale rings on the order sheet „How to Order Graduations“ → Page 326

see also...

- Applications and More Information to GN 200 → Page 353
- Indexing Mechanism GN 200 (Steel) → Page 352

How to order

GN 200-52-K12-AS-NI

1	d ₁
2	d ₂
3	Type
4	Material