



3 Type

- E** Angled lever
- D** Straight lever

1

2

d ₁	d ₂		d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄ ≈		h ₅ Stroke	l ₂ ≈		l ₃ ≈	t min.	
	M 6	M 8							Type E	Type D		Type E	Type D			
21	M 6	M 8	-	13,5	8	20	33,5	31	1	59	36	4	75	80,5	70	11
24	M 8	M 10	-	16	10	25	40	37	2,5	75	43,5	4,5	101	108	96	14
28	M 10	M 12	-	19	12	30	48,5	44,5	4,5	89	52,5	4,5	116	124	110	17
33	M 12	M 14	M 16	23	12	32	55	51,5	6	100,5	60	5,5	131,5	140,5	124	22
40	M 16	M 20	-	28	14	35	68	64	6	118	71,5	5,5	148	158	138	36

Specification

- Steel
Blackened
- Ball knobs DIN 319
Plastic, Duroplast
Black, shiny finish
- Safety circlip
Plastic (Polyacetal POM)
- *Plastic Characteristics* → Page 2158
- **RoHS**

On request

- With inch threads

Information

Adjustable tension levers GN 212.3 have proved to be ideal whenever parts have to be clamped in a confined space or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swiveled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- *Adjustable Stainless Steel Tension Levers GN 212.5* → Page 482
- *Safety Tension Levers GN 312* → Page 496

How to order

GN 212.3-24-M8-D

- 1** d₁
- 2** d₂
- 3** Type