



1

2

d ₁	s ₁ Square (conical)	s ₂	d ₂	l ₁	l ₂ ±1	No. of spokes	Thickness of pressed steel
125	VK 11	12,7	28	17	31	3	1,2
150	VK 12	13,8	30	18	33,5	3	1,5
200	VK 14	16	35	20	40,5	3	2
250	VK 17	19,25	36	23	47	4	2
300	VK 19	21,8	42	28	59	5	2
400	VK 24	27	48	30	66	5	2,5

Specification

3

Pressed steel

Cathodic dip coated (KTL)

- Black, RAL 9005
- Red, RAL 3000
- Hub
- Steel, welded

- SWK
- RTK

RoHS

On request

- With bore B
- With square V
- Neutral, no labeling

Handwheels GN 227.7 feature high mechanical strength and a coating for increased corrosion resistance. They are also not affected by shock and knocks.

The conical square hole allows easy installation and firm seating on a spindle. The cast shape prevents injuries from sharp edges during handling. The engraved labels “SHUT” and “OPEN” help with safe and correct operation of the valves.

see also...

GN 227.6 Handwheels

Page

QVX

Accessory

GN 184 Countersunk Washers

QVX

How to order

1	d ₁
2	s ₁
3	Color

GN 227.7-200-VK14-SWK