



1.1

1.2

1.3

1.4

1

2

$d_{1+0,5}$	$d_2$	$d_3$	$l_1$	$l_2$ min.	$l_3$
24	M 8	20,5	65	30	7
24	M 10	20,5	65	40	7
26	M 8	21	80	40	7
26	M 10	21	80	55	7
26	M 12	21	80	55	7
28	M 10	22	90	56	7
28	M 12	22	90	58	10

Specification

- Base body  
Plastic  
Technopolymer (Polypropylen PP)
- Softline coating
  - Elastomer (TPE) 70 Shore A
  - Chemically bonded with base body
  - FDA compliant plastic granulate
  - Temperature resistant up to 80 °C
  - Black, matte finish
- Plastic Characteristics → Page 2158
- RoHS

Information

The softline coating makes the cylindrical knobs GN 519.6 particularly user-friendly and ergonomic.

The **soft, slip-proof** contact area improves the contact both in hot (hand perspiration) and in dry ambient conditions, in the event of oily surfaces and even high or low temperatures.

see also...

- Product Family Softline → Page 18
- Cylindrical Knobs GN 519 (with Thread) → Page 68
- Cylindrical Knobs GN 519.1 (Press-On Type) → Page 72

2.1

2.2

2.3

2.4

How to order

GN 519.6-26-M10

1  $d_1$

2  $d_2$

