



**3 Type**

- S** With face and pointer
- Z** With pointer

**1**

**2**

d <sub>1</sub> Type S	Type Z	d <sub>2</sub> H9 Bore	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	e	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	l <sub>1</sub>	l <sub>2</sub>
32	-	B 6	14	19	-	M 4	36	6	27	-	3	-	19	19	-
40	40	B 6	14	21	25	M 4	45	6	30	27	3	2	14	24	25
50	50	B 8	15	25	30	M 5	56	7	36	33	3	2	20	30	31
60	60	B 8	15	27	32	M 5	70	7	42	37	5	2	20	37	38
70	70	B 10	18	30	35	M 6	80	10	48	44	5	2	25	42	45

**Specification**

- Plastic  
Knob: Duroplast (PF)  
Pointer: Technopolymer (Polyamide PA)  
- Temperature resistant up to 110 °C  
- Black, shiny finish
- Bushing  
Brass: Size 32, 40  
Steel: Size 50, 60, 70
- Arrow (Type S)  
White
- Grub screw DIN 916  
with internal hexagon and serrated point
- *ISO Fundamental Tolerances* → Page 2151
- *Plastic Characteristics* → Page 2158
- RoHS

**Information**

Setting knobs GN 5338 are very appealing with a good gripping feel. The manufacturing technique has made it possible to produce them with no visible flash mark.

The indicator element is slid onto the handle hub and secured against rotation.

**Two** studs with a serrated point ensure proper fastening on the shaft.

How to order

**GN 5338-50-B8-S**

- 1** d<sub>1</sub>
- 2** d<sub>2</sub>
- 3** Type