Knurled Knobs

Plastic, Threaded Bushing Brass





elesa
Original design MBT.





1		2	2					
d_1 Nominal dimension	Actual dimension	**d_2** Thread	**d_3** H9 Bore	**d_4**	**h_1**	**h_2**	**t_1** min.	**t_2** min.
32	31	M 5	-	15	24	11,5	10	-
32	31	M 6	-	15	24	11,5	12	-
40	39,5	M 6	B 6	17	26,5	12,5	12	14
40	39,5	M 8	-	17	26,5	12,5	13	-
50	50	M 8	B 8	20	33	16	20	20
50	50	M 10	-	20	33	16	18	-
60	61	M 10	B 10	23	39	18,5	20	25
60	61	M 12	-	23	39	18,5	20	-
70	70	M 12	-	24	42	20,5	20	-
70	70	M 14	-	24	42	20,5	20	-

Specification

Knob
Plastic, Polypropylen (PP)
- Reinforced, shock resistant
- Black, RAL 9005, matte finish ● **SW**

Threaded bushing
Brass

Cover cap
Plastic, Polyamide (PA)

• Black, RAL 9005, matte finish	● –
• Orange, RAL 2004, matte finish	● **DOR**
• Gray, RAL 7035, matte finish	● **DGR**
• Yellow, RAL 1021, matte finish	● **DGB**
• Blue, RAL 5024, matte finish	● **DBL**
• Red, RAL 3000, matte finish	● **DRT**
• Green, RAL 6017, matte finish	● **DGN**

Operating temperature 0 °C to +90 °C

RoHS

The unique profileon the rim (small squares) of the knurled knobs GN 534 is characteristic of its form and the function.

see also...	Page
GN 735 Control Handwheels	QVX
GN 7336 Knurled Knobs	QVX
GN 4534 Knurled Knobs (Softline)	QVX
GN 534 Knurled Knobs (with Loss protections GN 111.7)	QVX

Technical Information

Cross holes GN 110 (Special Order)	QVX
ISO Fundamental Tolerances	QVX
Plastic Characteristics	QVX

How to order (Cover cap black)

1 2 3
GN 534-40-M8-SW

1	d_1
2	d_2 (d_3)
3	Color (Knob)

How to order (Cover cap colored)

1 2 3 4
GN 534-50-M10-SW-DRT

1	d_1
2	d_2 (d_3)
3	Color (Knob)
4	Color (Cover cap)