



Flat shoulder screw DIN 923

1

2

d ₁	b	d ₂	d ₃	l ₁	l ₂	l ₃	l ₄	s -0,5	Screw DIN 923
38	7,5	9	6	19,6	11	29	19	9,8	M 6 x 10
43	9,5	9	8	21,6	14	32,5	21	9,8	M 6 x 10
48	11,5	9	10	23,6	17	36,5	23	9,8	M 6 x 10
61	13,5	11	12	29,6	22	45	29	11,8	M 8 x 12
68	17,5	11	16	33,6	25	50	33	11,8	M 8 x 12
74	21,5	11	20	36,6	28	55	36	11,8	M 8 x 12
82	25,5	11	24	40,6	32	62	40	15,8	M 8 x 16
97	32	11	30	49	39	73	48	15,8	M 8 x 16

Specification

- Steel
 - Tempered
 - Blackened
- Flat shoulder screw DIN 923
 - Blackened
- RoHS

Information

Captive C-Washers DIN 6371 transfer the clamping force of screw or nut to the workpiece. After releasing the thread they can be swung away from the clamping point. They are hinged and thus can never be mislaid.

Flat shoulder screws DIN 923 are included in the delivery.

How to order

DIN 6371-48-11,5

1 d₁

2 b