


Assembly options



d₁	l₁	a₁	a₂	a₃	d₂	d₃ -0,3	d₄	k	l₂	l₃	A/F
M 3	12	1,5-3	3-6,5	6,5-8	5,5	2,2	3,5	2	4	1,5	2
M 3	16	3-7	7-8	8-12	5,5	2,2	3,5	2	4	1,5	2
M 4	16	2-5	5-8	8-11	7	3	4,5	2,8	5	2	2,5
M 4	20	5-9	9-11	11-15	7	3	4,5	2,8	5	2	2,5
M 5	20	2,5-6	6-10,5	10,5-14	8,5	3,9	5,5	3,5	6	2,5	3
M 5	25	6-11	11-14	14-19	8,5	3,9	5,5	3,5	6	2,5	3
M 6	25	3-7	7-13	13-17	10	4,5	6,5	4	8	3	4
M 6	30	7-12	12-17	17-22	10	4,5	6,5	4	8	3	4
M 8	30	4-8	8-16	16-20	13	6,3	8,5	5	10	4	5
M 8	35	8-13	13-20	20-25	13	6,3	8,5	5	10	4	5
M 8	40	13-18	18-25	25-30	13	6,3	8,5	5	10	4	5

Specification

Stainless steel AISI 304

RoHS



NI

Socket cap screws GN 7984.2 have a low-profile head to enable use in areas with limited space.

Due to a recessed stud d_3 , the screw can be easily secured against loss, for example in a cover. Thus the „captive of the mounting element“ according to the Machinery Directive 2006 / 42 / EG is given.

For this purpose, instead of a normal through / threaded hole a thread d_1 on both sides, if necessary with a corresponding clearance hole d_4 must be provided. Depending on the design and required clamping length $a_1 \dots a_3$ of the cover, there are a number of assembly options as shown.

see also...

GN 912.2 Socket Cap Screws

GN 7045.2 Pan Head Screws (with Phillips Drive)

Technical Information

Stainless Steel Characteristics

Page

QVX

QVX

QVX

How to order

GN 7984.2-M8-40-NI

1	d ₁
2	l ₁
3	Material